



USlimO P3.9 - 500x1000 Outdoor

SKU: LV1937 Model: USlimO P3.9 - 500x1000 Outdoor

| Parameter                            | Unit                        | Value   |  |
|--------------------------------------|-----------------------------|---|--|
| <b>Display technology</b>            | Pixel Pitch                 | mm (inch)   | 3.9  |
|                                      | Brightness                  | nits  | 5500   |
|                                      | Viewing Angle - Horizontal  | deg.  | 140  |
|                                      | Viewing Angle - Vertical    | deg.  | 120  |
|                                      | Pixel Type & Configuration  | RGB   | 3-in-1 SMD   |
|                                      | Resolution per Cabinet      | -   | 128(w) x 256(h)  |
|                                      | Dot per Cabinet             | -   | 32768  |
|                                      | Dot per sq. Meter           | -   | 65536  |
|                                      | Colours                     | -   | 16.5 million   |
|                                      | Grey Scale (linear)         | Levels  | 65,365 levels per colour                                   |
|                                      | Contrast Ratio              | -   | 3000:1   |
|                                      | Display Refresh Rate        | Hz  | 1920   |
|                                      | <b>Physical</b>             | Cabinet Width   | mm (inch)  |
| Cabinet Height                       |                             | mm (inch)   | 1000 (39.3701)   |
| Cabinet Depth                        |                             | mm (inch)   | 83.3 (3.27952933)  |
| Cabinet Weight                       |                             | Kg  | 13   |
| Cabinet Area                         |                             | Sq. m.  | .5   |
| Cabinet Material                     |                             | -   | Die-cast aluminum  |
| Cabinet Type                         |                             | -   | Indoor - rental and staging                                |
| Recommended Minimum Viewing Distance |                             | m   | 3.9  |
| Recommended Best Viewing Distance    |                             | m   | 4.9  |
| Mounting System                      |                             | Hanging or 4x8mm bolts (m8)   |  |
| <b>Environment</b>                   | Operating Temperature Range | deg. C  | 0 - 50   |
|                                      | Humidity Operating Range    | RH  | 10 -90   |
|                                      | Lifetime                    | Hours   | 100,000  |
| <b>Power</b>                         | Input Voltage (nominal)     | VAC   | Unable to pull dynamic data, please contact your sales rep |
|                                      | Power Draw                  | W/Cabinet Avg (Max)   | Unable to pull dynamic data, please contact your sales rep |
|                                      | Current (120V @ 60Hz)       | Amps Avg (Max)  | Unable to pull dynamic data, please contact your sales rep |
| <b>Warranty</b>                      | Manufactured Warranty       | Manufactured in China<br>year manufacturers warranty on part defects.<br>LIGHTVU extended warranty up to years. |  |
|                                      |                             |   |  |
| <b>Certifications</b>                | CEC Certification           | CE, FCC, RoHS, cETL   |  |



Due to constant research and product development, specifications subject to change without notice.

