



USlimO P3.9 - 500x500 Outdoor

SKU: LV1938 Model: USlimO P3.9 - 500x500 Outdoor

Parameter	Unit	Value	
Display technology	Pixel Pitch	mm (inch)	3.9
	Brightness	nits	5500
	Viewing Angle - Horizontal	deg.	140
	Viewing Angle - Vertical	deg.	120
	Pixel Type & Configuration	RGB	3-in-1 SMD
	Resolution per Cabinet	-	128(w) x 128(h)
	Dot per Cabinet	-	16384
	Dot per sq. Meter	-	65536
	Colours	-	16.5 million
	Grey Scale (linear)	Levels	65,365 levels per colour
	Contrast Ratio	-	3000:1
	Display Refresh Rate	Hz	1920
	Physical	Cabinet Width	mm (inch)
Cabinet Height		mm (inch)	500 (19.68505)
Cabinet Depth		mm (inch)	83.3 (3.27952933)
Cabinet Weight		Kg	8
Cabinet Area		Sq. m.	0.25
Cabinet Material		-	Die-cast aluminum
Cabinet Type		-	Indoor - rental and staging
Recommended Minimum Viewing Distance		m	3.9
Recommended Best Viewing Distance		m	4.9
Mounting System		Hanging or 4x8mm bolts (m8)	
Environment	Operating Temperature Range	deg. C	0 - 50
	Humidity Operating Range	RH	10 -90
	Lifetime	Hours	100,000
Power	Input Voltage (nominal)	VAC	Unable to pull dynamic data, please contact your sales rep
	Power Draw	W/Cabinet Avg (Max)	Unable to pull dynamic data, please contact your sales rep
	Current (120V @ 60Hz)	Amps Avg (Max)	Unable to pull dynamic data, please contact your sales rep
Warranty	Manufactured Warranty	Manufactured in China year manufacturers warranty on part defects. LIGHTVU extended warranty up to years.	
Certifications	CEC Certification	CE, FCC, RoHS, cETL	



Due to constant research and product development, specifications subject to change without notice.

