



USlim-II P3.2 - 500x1000

SKU: LV2756 Model: USlim-II P3.2 - 500x1000

Parameter	Unit	Value	
Display technology	Pixel Pitch	mm (inch)	3.2
	Brightness	nits	1000
	Viewing Angle - Horizontal	deg.	Unable to pull dynamic data, please contact your sales rep
	Viewing Angle - Vertical	deg.	Unable to pull dynamic data, please contact your sales rep
	Pixel Type & Configuration	RGB	3-in-1 SMD
	Resolution per Cabinet	-	156(w) x 312(h)
	Dot per Cabinet	-	48672
	Dot per sq. Meter	-	97344
	Colours	-	16.5 million
	Grey Scale (linear)	Levels	65,365 levels per colour
	Contrast Ratio	-	Unable to pull dynamic data, please contact your sales rep
	Display Refresh Rate	Hz	Unable to pull dynamic data, please contact your sales rep
	Physical	Cabinet Width	mm (inch)
Cabinet Height		mm (inch)	1000 (39.3701)
Cabinet Depth		mm (inch)	Unable to pull dynamic data, please contact your sales rep
Cabinet Weight		Kg	10.5
Cabinet Area		Sq. m.	.5
Cabinet Material		-	Die-cast aluminum
Cabinet Type		-	Indoor - rental and staging
Recommended Minimum Viewing Distance		m	3.2
Recommended Best Viewing Distance		m	4.2
Mounting System		Hanging or 4x8mm bolts (m8)	
Environment	Operating Temperature Range	deg. C	0 - 50
	Humidity Operating Range	RH	10 -90
	Lifetime	Hours	100,000
Power	Input Voltage (nominal)	VAC	Unable to pull dynamic data, please contact your sales rep
	Power Draw	W/Cabinet Avg (Max)	Unable to pull dynamic data, please contact your sales rep
	Current (120V @ 60Hz)	Amps Avg (Max)	Unable to pull dynamic data, please contact your sales rep
Warranty	Manufactured	Manufactured in China	
	Warranty	year manufacturers warranty on part defects. LIGHTVU extended warranty up to years.	
Certifications	CEC Certification	CE, FCC, RoHS, cETL	



Due to constant research and product development, specifications subject to change without notice.

