



USlimO P3.9 - 500x1000 Outdoor - 4500 nits

SKU: LV2794 Model: USlimO P3.9 - 500x1000 Outdoor - 4500 nits

Parameter	Unit	Value	
<b>Display technology</b>	Pixel Pitch	mm (inch)	3.9
	Brightness	nits	4500
	Viewing Angle - Horizontal	deg.	140
	Viewing Angle - Vertical	deg.	120
	Pixel Type & Configuration	RGB	3-in-1 SMD
	Resolution per Cabinet	-	128(w) x 256(h)
	Dot per Cabinet	-	32768
	Dot per sq. Meter	-	65536
	Colours	-	16.5 million
	Grey Scale (linear)	Levels	65,365 levels per colour
	Contrast Ratio	-	3500:1
	Display Refresh Rate	Hz	1920
	<b>Physical</b>	Cabinet Width	mm (inch)
Cabinet Height		mm (inch)	1000 (39.3701)
Cabinet Depth		mm (inch)	83.3 (3.27952933)
Cabinet Weight		Kg	13
Cabinet Area		Sq. m.	.5
Cabinet Material		-	Die-cast aluminum
Cabinet Type		-	Indoor - rental and staging
Recommended Minimum Viewing Distance		m	3.9
Recommended Best Viewing Distance		m	4.9
Mounting System		Hanging or 4x8mm bolts (m8)	
<b>Environment</b>	Operating Temperature Range	deg. C	0 - 50
	Humidity Operating Range	RH	10 -90
	Lifetime	Hours	100,000
<b>Power</b>	Input Voltage (nominal)	VAC	Unable to pull dynamic data, please contact your sales rep
	Power Draw	W/Cabinet Avg (Max)	Unable to pull dynamic data, please contact your sales rep
	Current (120V @ 60Hz)	Amps Avg (Max)	Unable to pull dynamic data, please contact your sales rep
<b>Warranty</b>	Manufactured Warranty	Manufactured in China year manufacturers warranty on part defects. LIGHTVU extended warranty up to years.	
<b>Certifications</b>	CEC Certification	CE, FCC, RoHS, cETL	



Due to constant research and product development, specifications subject to change without notice.

